

CBD18/20-180 1.8-2.0 Ton Electric Pedestrian Pallet Trucks

Advantages

- Mechanical Steering-Economic, comfortable, more reliable.
- AC Driving System-Low noise, quiet, without carbon brush and free maintenance.
- Electric Lifting-Rapid, efficient, electricity limit switch is standard.
- Short Wheelbase-Small turning radius, suitable for narrow space.
- Excellent Design-Easily in and out of the double tray.
- Energy conservation-Save energy, every day only 5kW/h.
- AC Controller-Stepless, stong power, multiple automatic protection.

Options

- 140Ah VRLA Battery+Built-in charger.
- Handle upright walking function.



AC | Short wheelbase

Fork suitable for reversible pallet

Higher performance at best price Most popular in Europe & America





TOP1 FORKLIFT MANUFACTURER AND SALER IN CHINA FOR CONSECUTIVE 25 YEARS

H⊑∟ CBD18/20-180

Feature		
Model		CBD18/20
Configuration No.		180
Loading capacity	kg	1800/2000
Load center	mm	600
Wheel base	mm	1300
Operating type		Pedestrian
Wheels		recestran
Wheels type		PU
Wheel quantity Driving wheel/Balance wheel/Bearing wheel		1/1/4
Driving wheel size	mm	C228×75
Bearing wheel size	mm	€84×80(Double wheels)
Balance wheel size	mm	©115×55
Dimension		£113×33
Min.fork lowered height	mm	85
Max.fork lifting height	mm	195
Max.lifting height	mm	110
Overall fork width	mm	550/600/650/685
Inside width between forks	mm	210/260/310/345
Fork length	mm	1150/1200
Forkwidth	mm	170
Fork thickness	mm	75
Overall length	mm	1650
Overall width	mm	725
Overall height(With handle)	mm	1380
Overall height(Without handle)	mm	890
Min.Turning radius	mm	1450
Min.Aisle width for pallets 800×1200	mm	1866
Min.Aisle width for pallets 1000×1200	mm	1921
Performance		1721
Travel speed,laden/unladed	km/h	3.5/4.0
Lift speed,laden/unladed	mm/s	30/35
Lowering speed, laden/unladed	mm/s	40/35
Gradeability,laden/unladed	%	5/7
Electrical configuration	70	5//
Drive motor	kW	AC 0.93
Drive motor	kW	DC 1.2
Steering motor	kW	DC 1.2
Battery voltage / capacity	V/Ah	24/210
Battery voltage / capacity Brake	V/AII	
Controller		Electromagnetic/Regenerative
Controller Weight		CURTIS
	li e	202
Battery weight Service weight with battery	kg	202
service weight with pattery	kg	552

^{*} Details of specifications and equipment are based on information available at time of printing and may change without notice.







ANHUI HELI CO., LTD.

ADD: NO.668 Fangxing Street, Economical Development Zone, Hefei, P.R. China TEL: (86 551)63639068, 63639258, 63639358, 63662105, 63639530

FAX: (86 551)63639966 WEBSITE: http://www.helichina.net Email: heli@helichina.net



AUTHORIZED DEALER